

BIRMINGHAM ankle safety shoes

» Shoes » Safety shoes » Ankle

Technical sheet

BIRMINGHAM ankle safety shoes

Product code: 8020-S7L



upper	UPPER breathable poromeric microfiber material
lining	vapor permeable, waterproof GORE-TEX® membrane
inner insole	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	PU/TPU - SR, resistant to fuel oils, slip resistant, antistatic
size	37 - 48
standard	EN ISO 20345:2022
version	S7L FO SR - with composite toe cap and kevlar midsole, hydrophobic, GORE-TEX® membrane

Properties

PL Midsole penetration protection nonmetallic - PL	Yes
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	Yes
WPA Water resistant upper	Yes
HRO Resist. of the outsole against contact heat	No
WR Water resistant	Yes

BIRMINGHAM ankle safety shoes

» Shoes » Safety shoes » Ankle

WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2023
Shoe marking	S7

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
37	1,27 kg	1,66 kg	285 mm	330 mm	125 mm	590 mm	650 mm	360 mm	18,00 kg	0,0 mm
38	1,29 kg	1,69 kg	285 mm	330 mm	125 mm	590 mm	650 mm	360 mm	18,20 kg	0,0 mm
39	1,37 kg	1,76 kg	285 mm	330 mm	125 mm	590 mm	650 mm	360 mm	19,00 kg	0,0 mm
40	1,43 kg	1,82 kg	285 mm	330 mm	125 mm	590 mm	650 mm	360 mm	19,60 kg	0,0 mm
41	1,48 kg	1,86 kg	285 mm	330 mm	125 mm	590 mm	650 mm	360 mm	20,00 kg	0,0 mm
42	1,53 kg	1,92 kg	285 mm	330 mm	125 mm	590 mm	650 mm	360 mm	21,60 kg	0,0 mm
43	1,58 kg	2,02 kg	305 mm	370 mm	130 mm	630 mm	670 mm	400 mm	21,80 kg	0,0 mm
44	1,62 kg	2,05 kg	305 mm	370 mm	130 mm	630 mm	670 mm	400 mm	22,00 kg	0,0 mm
45	1,70 kg	2,14 kg	305 mm	370 mm	130 mm	630 mm	670 mm	400 mm	22,80 kg	0,0 mm
46	1,72 kg	2,16 kg	305 mm	370 mm	130 mm	630 mm	670 mm	400 mm	23,00 kg	0,0 mm
47	1,77 kg	2,21 kg	305 mm	370 mm	130 mm	630 mm	670 mm	400 mm	23,40 kg	0,0 mm
48	1,86 kg	2,30 kg	305 mm	370 mm	130 mm	630 mm	670 mm	400 mm	24,20 kg	0,0 mm

Business parameters

Tarric	64041990
Country	CN
Weight	2,20 kg
Add Unit	NPR

BIRMINGHAM ankle safety shoes

» Shoes » Safety shoes » Ankle

Add Quantity 1